





PIN NO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SEGMENT	COM	□	B-C	NC	NC	NC	NC	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B
PIN NO	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
SEGMENT	1A	1F	1G	2B	2A	2F	2G	COL	3B	3A	3F	3G	NC	NC	NC	NC	NC	LO BAT	□	COM

1.ALL DIMENSIONS ARE IN mm WITH ± 0.20
TOLERANCE UNLESS OTHERWISE SPECIFIED.
2.VIEWING ANGLE: 6:00 O'CLOCK.
3.VIEWING MODE: POSITIVE, REFLECTIVE
4.DISPLAY TYPE : TN
5.CONNECTION: PIN
6.FLUID SPECIFICATION:
DRIVING VOLTAGE: 3.0--5.0V
MULTIPLEX LEVEL: STATIC
OPERATING TEMP. -20°C -- +70°C
STORAGE TEMP. : -30°C -- +80°C

奈格科技有限公司
Nergal Technology Co., Ltd



客户确认:

绘图:

绘图编号: NT-127

单位: mm

审核:

客户编号: 1

日期: 2004.07.16

批准:

图纸版号: 01

页数: 1/3